

Архангельск (8182)63-90-72
 Астана (7172)727-132
 Астрахань (8512)99-46-04
 Барнаул (3852)73-04-60
 Белгород (4722)40-23-64
 Брянск (4832)59-03-52
 Владивосток (423)249-28-31
 Волгоград (844)278-03-48
 Вологда (8172)26-41-59
 Воронеж (473)204-51-73
 Екатеринбург (343)384-55-89
 Иваново (4932)77-34-06

Ижевск (3412)26-03-58
 Иркутск (395)279-98-46
 Казань (843)206-01-48
 Калининград (4012)72-03-81
 Калуга (4842)92-23-67
 Кемерово (3842)65-04-62
 Киров (8332)68-02-04
 Краснодар (861)203-40-90
 Красноярск (391)204-63-61
 Курск (4712)77-13-04
 Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
 Москва (495)268-04-70
 Мурманск (8152)59-64-93
 Набережные Челны (8552)20-53-41
 Нижний Новгород (831)429-08-12
 Новокузнецк (3843)20-46-81
 Новосибирск (383)227-86-73
 Омск (3812)21-46-40
 Орел (4862)44-53-42
 Оренбург (3532)37-68-04
 Пенза (8412)22-31-16

Пермь (342)205-81-47
 Ростов-на-Дону (863)308-18-15
 Рязань (4912)46-61-64
 Самара (846)206-03-16
 Санкт-Петербург (812)309-46-40
 Саратов (845)249-38-78
 Севастополь (8692)22-31-93
 Симферополь (3652)67-13-56
 Смоленск (4812)29-41-54
 Сочи (862)225-72-31
 Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
 Тверь (4822)63-31-35
 Томск (3822)98-41-53
 Тула (4872)74-02-29
 Тюмень (3452)66-21-18
 Ульяновск (8422)24-23-59
 Уфа (347)229-48-12
 Хабаровск (4212)92-98-04
 Челябинск (351)202-03-61
 Череповец (8202)49-02-64
 Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://otechmakine.nt-rt.ru/> || ona@nt-rt.ru

Rectified Servo Drives



- Induction Grinding Roller Set
- Geared Servo Motor Drive
- Pneumak Plotting System
- Manual Reducer Moving Rectifier Pressure
- Able to Adjust Height (Elevator Table Type)
- Kiosk Operator Panel, 7" Touch Screen
- Mould Storage for Easy Use
- Multi-Dimension Sheeting mode
- PLC Control
- Joysck Button for Easy Use During Mold Adjustment

- Product Range of -400 - 1300 mm Width
- -0.50 - 4.00 mm Sheet Thickness Range
- Kiosk Operator Panel for Comfortable Use of Operators
- -7 - 9 - 11 - 13 Straightening and Sliding Roller Models
- Possibility of Height Adjustment After Installation

Model	Material Width Max. material "Width (mm) "	Sheet Metal Thickness Sheet Metal Thickness "Thickness (mm) "		Free Ride speed Free Driving Speed " Speed (m/min.) "	Rollers rollers	Control System
		min	Max			
OT-DSS-G300	30-300mm	0.30 – 2.50mm		32 m/min	Ø 85 - 2+5	Servo
OT-DSSCS-G300	30-300mm	0.30 – 2.50mm		32 m/min	Ø 85 - 2+5+2	Servo
OT-DSS-G400	40-400mm	0.30 – 2.50mm		32 m/min	Ø 85 - 2+5	Servo
OT-DSSCS-G400	40-400mm	0.30 – 2.50mm		32 m/min	Ø 85 - 2+5+2	Servo
OT-DSS-G600	60-600mm	0.30 – 2.50mm		32 m/min	Ø 85 - 2+5	Servo
OT-DSSCS-G600	60-600mm	0.30 – 2.50mm		32 m/min	Ø 85 - 2+5+2	Servo
OT-DSS-G800	70-800mm	0.30 – 2.50mm		32 m/min	Ø 85 - 2+5	Servo
OT-DSSCS-G800	70-800mm	0.30 – 2.50mm		32 m/min	Ø 85 - 2+5+2	Servo
OT-DSS-G1000	150-1000mm	0.30 – 2.50mm		32 m/min	Ø 85 - 2+5	Servo
OT-DSSCS-G1000	150-1000mm	0.30 – 2.50mm		32 m/min	Ø 85 - 2+5+2	Servo
OT-DSS-G1300	400-1300mm	0.30 – 2.50mm		32 m/min	Ø 85 - 2+5	Servo
OT-DSSCS-G1300	400-1300mm	0.30 – 2.50mm		32 m/min	Ø 85 - 2+5+2	Servo